



# Rubber Washers



The outside diameter dimensions listed as standard are based on “Pan Head” metal screw dimensions delineated in U.S.A.S. B 19.6.4. The outside diameters listed as optional are based on standard S.A.E. steel washers common to the trade. Standard thickness is 3/32”, additional thicknesses are available.

SCREW SIZE	PART NUMBER	OUTSIDE DIAMETER	INSIDE DIAMETER
#6 Standard	R 0250 12 T	1/4” 6.3mm	.120” 3mm
#6 Optional	R 0375 12 T	3/8” 9.5mm	.120” 3mm
#8 Standard	R 0313 15 T	5/16” 8mm	.150” 3.8mm
#8 Optional	R 0438 15 T	7/16” 11mm	.150” 3.8mm
#10 Standard	R 0375 17 T	3/8” 9.5mm	.170” 4.3mm
#10 Optional	R 0500 17 T	1/2” 13mm	.170” 4.3mm
#12 Standard	R 0438 20 T	7/16” 11mm	.195” 5mm
#12 Optional	R 0562 20 T	9/16” 14mm	.195” 5mm
#14 Standard	R 0500 23 T	1/2” 13mm	.230” 5.8mm
#14 Optional	R 0625 23 T	5/8” 16mm	.230” 5.8mm
5/16” Standard	R 0562 29 T	9/16” 14mm	.290” 7.4mm
5/16” Optional	R 0688 29 T	11/16” 17.5mm	.290” 7.4mm
3/8” Standard	R 0625 35 T	5/8” 16mm	.355” 9mm
3/8” Optional	R 0812 35 T	13/16” 9.5mm	.355” 9mm
1/2” Optional	R 1062 49 T	1-1/16” 27mm	.490” 12.4mm
5/8” Optional	R 1312 62 T	1-5/16” 33.3mm	.615” 15.6mm
3/4” Optional	R 1500 74 T	1-1/2” 19mm	.740” 18.8mm
1” Optional	R 2000 99 T	2” 51mm	.990” 25mm



### Features:

- EPDM Rubber
- Available in custom sizes



### Applications:

- cushioning • sealing
- abrasion • vibration or dampening.

